

HERCULUX™

H612 SERIES – DEEP PROFILE HOUSING

PRODUCT FEATURES:

- » Surface wall mount – nominal 6"W×12"L×7"D
- » Heavy die-cast aluminum housing
- » UV-stabilized, injection molded polycarbonate lens
- » Stainless steel Torx® fasteners



PROJECT INFORMATION

Job Name _____

Fixture Type _____

Catalog Number _____

Approved by _____

SPECIFICATIONS

HOUSING: One-piece heavy duty die-cast, low-copper aluminum housing. Housing flange interlocks around lens producing maximum moisture deflection and resistance to prying. Housing provided with four standoff mounting holes. One 3/4" IPS tapped hole on back of housing. Two 3/4" IPS tapped and plugged holes on top and bottom of housing – see Cross Section/Details. Standard housing in dark bronze TGIC polyester powder coat – 5-stage pre-treatment.

REFLECTOR: High reflectance painted aluminum.

LENS: One-piece wraparound lens (UV-stabilized, high impact, virgin injection molded polycarbonate). Smooth exterior, prismatic interior. Nominal thickness: 0.125".

EYELID: High-impact resistant, UV-stabilized injection molded opaque dark bronze polycarbonate. See Ordering Information for optional finishes to match housing.

GASKET: Die-cut closed cell neoprene gasket seals die-cast housing to mounting surface. Lens inset into housing and sealed to integral ledge with one "O" ring closed cell silicone gasket.

HARDWARE: Four captive stainless steel Torx® T-20 with center pin fasteners secure lens/eyelid to housing. Shoulder fastener design and washer prevent lens/eyelid stress due to over torquing.

ELECTRICAL: Available in 3500K, 4000K, and 5000K color temperatures, 80 CRI. 120-277VAC or 347VAC, 50/60Hz electrical input with high power factor electronic, constant-current driver (>.90 PF). Standard 0-10V dimming with 1-100% range; maximum driver source of 200 µA.

SENSOR & CONTROLS: Optional sensor available with compatible third party controls. To see the full list of compatible controls, [click here](#).

INSTALLATION: Wall mount fixture must be installed lamp base up. Standard four-point mounting required for Peace of Mind Guarantee®.

PHOTOMETRICS: Photometry tested to the IESNA LM-79-08 standard by an ILAC/ISO17025 accredited laboratory. For additional photometric data, please go to www.kenall.com.

WARRANTY: Limited five (5) year LED warranty. [Peace of Mind Guarantee against breakage](#).

LISTINGS: Luminaire is certified to UL Standards by Intertek Testing Laboratory for Wet Location. Luminaire tested to an IK10 impact protection rating per IEC 60068-2-75:1997-08.



ORDERING INFORMATION (Ex: H612FD-PP-MB-25L40K-DV)

Model	Lens Type	Finish	Lamp Type	Voltage	Options
PP					
Model			Lamp Type		Options
H612ED	Eyelid		15L35K 15 Watt 3500K LED		BPC Photo Control – Button Type (120 or 277V only)
H612FD	Full Face		15L40K 15 Watt 4000K LED		LEL† LED Emergency Battery Backup (n/a with 347V, n/a with 25L)
			15L50K 15 Watt 5000K LED		FS Single Fuse & Holder
Lens Type			25L35K 25 Watt 3500K LED		20KV† 20KV/KA Surge Protection per IEEE/ANSI C62.41.2 Cat. A
PP	Pearlescent Polycarbonate		25L40K 25 Watt 4000K LED		
			25L50K 25 Watt 5000K LED		
Finish			Voltage		
DB	Dark Bronze		120 120 Volts		
MB	Matte Black		277 277 Volts		
MW	Matte White		347▲ 347 Volts		
LG	Light Gray		DV▲ 120-277 Volts		
SL	Silver				† LEL and 20KV options not available in conjunction
FG	Forest Green				▲ n/a with BPC
CC	Custom Color (Consult factory)				



www.kenall.com | P: 800-4-Kenall | F: 262-891-9700 | 10200 55th Street Kenosha, Wisconsin 53144, USA
 This product is able to comply with the latest domestic preference legislation, such as the Buy American Act (BAA), Trade Agreement Act (TAA), Build America, Buy America Act (BABA), and others. It may be covered by patents found at www.kenall.com/patents. Content of specification sheets is subject to change; please consult www.kenall.com for current product details. ©2024 Kenall Mfg. Co.

A brand of Legrand

This product is able to comply with the latest domestic preference legislation, such as the Buy American Act (BAA), Trade Agreement Act (TAA), Build America, Buy America Act (BABA), and others. It may be covered by patents found at www.kenall.com/patents. Content of specification sheets is subject to change; please consult www.kenall.com for current product details. ©2024 Kenall Mfg. Co.

HERCULUX™


H612 SERIES – DEEP PROFILE HOUSING

PERFORMANCE

Model	Lamp Type	Initial Delivered Lumens		Input Power (W)	Drive Current (mA)	Estd. L70 LED Life (Hrs)
		@ 25°C	Efficacy (lm/W)			
H612ED	15L35K	1349	72	19	140	85,000
	15L40K	1349	72	19	140	85,000
	15L50K	1470	79	19	140	85,000
	25L35K	2164	74	29	117	85,000
	25L40K	2164	74	29	117	85,000
	25L50K	2359	81	29	117	85,000
H612FD	15L35K	1959	99	20	140	85,000
	15L40K	1959	99	20	140	85,000
	15L50K	2135	108	20	140	85,000
	25L35K	2872	96	30	117	85,000
	25L40K	2872	96	30	117	85,000
	25L50K	3130	105	30	117	85,000


Information subject to change. Visit www.kenall.com for IES files and additional information.

Model: H612ED-PP-MW-25L40K-DV



Max Candela = 542 Located At Horizontal Angle = 0, Vertical Angle = 82.5
 1 - Vertical Plane Through Horizontal Angles (0-180) (Through Max. Cd.)
 2 - Horizontal Cone Through Vertical Angle (82.5) (Through Max. Cd.)


Model: H612FD-PP-MW-25L40K-DV



Max Candela = 599 Located At Horizontal Angle = 90, Vertical Angle = 17.5
 1 - Vertical Plane Through Horizontal Angles (90-270) (Through Max. Cd.)
 2 - Horizontal Cone Through Vertical Angle (17.5) (Through Max. Cd.)

DIMENSIONAL DATA

CROSS SECTION / DETAILS



BACK MOUNTING VIEW

