MEDMASTER SOFTSTEP™ STEPLIGHTS

Patient Room Steplight

MSL SERIES – FABRICATED

PRODUCT FEATURES:

- » Recessed wall mount Rectangle available in horizontal or vertical orientation
- » NSF2 listing for cleanability
- » White, Amber, or Red LED lamp options
- » ADA Compliant
- » Ligature resistant construction



MSLS





MSLR-H MSLR-V

SPECIFICATIONS

HOUSING: 18-gauge CRS. White TGIC polyester powder coat - 5-stage pre-treatment. Salt spray test: 1,000 hours; Reflectance: 92%. Four .875" knockouts.

FACEPLATE: 18-gauge CRS (powder coated) or Type 304 Stainless Steel. Faceplate secured to housing with stainless steel screws. Internal louver is positioned behind lens for easy cleaning of entire faceplate. See Faceplate Finish in Ordering Information for color selection.

LENS: Polycarbonate, acrylic or tempered glass lens. Polycarbonate and acrylic lens available in clear, prismatic or translucent white. Tempered glass available in clear or prismatic.

ELECTRICAL: 120VAC or 277VAC 60Hz input. Available in white, red, or amber LED.

INSTALLATION: Two adjustable mounting brackets for new construction.

PHOTOMETRICS: Photometry tested to the IESNA LM-79-08 standard by an ILAC/ISO17025 accredited laboratory. For additional photometric information, go to www.kenall.com.

WARRANTY: Limited five (5) year LED warranty.

LISTINGS: UL and CUL Listed for Damp Location. See Option for Wet Location listing. NSF2 Splash/Non-Food Zone. Ligature resistant construction.



ORDERING INFORMATION (Ex: MSLR-H-F-0-GW-CP-WLL-120-2)

Model	Faceplate	Faceplate Material	Faceplate Finish	Lens Type	Lamp Type	Voltage	Fasteners	Option	Packaging
-------	-----------	--------------------	------------------	-----------	-----------	---------	-----------	--------	-----------

Model

MSLR-V Rectangle Vertical MSLR-H Rectangle Horizontal

MSLS Sauare

Faceplate

Full Face Internal Louver

Slotted St

Faceplate Material

18-Ga CRS (Painted) 18-Ga Type 304 SS

Faceplate Finish

GW Gloss White Antimicrobial MW Matte White Antimicrobial MB Matte Black Antimicrobial

BE Beige Dark Bronze DB

LG Light Gray

ΙV Ivorv

Cool Satin Painted Anodized CS Warm Satin Painted Anodized WS Brushed SS (only available with BSS Faceplate Material Option 1)

Lens Type

Polycarbonate

Clear Polycarbonate

PР Pearlescent Polycarbonate

.125" #12 Prismatic Polycarbonate

<u>Acrylic</u>

.125" Clear High Impact Acrylic

PIA Pearlescent Acrylic

.125" #12 Prismatic High Impact Acrylic

Tempered Glass

.187" Clear Tempered Glass TG .188" Textured Tempered Glass

Lamp Type

Low Lumen

WLL 4000K White Low Lumen LED (0.05A/0.55W)

Amber LED (0.05A/0.50W) ALL

RLL Red LED (0.05A/0.50W)

High Lumen

WHL 4000K White High Lumen LED (0.10A/1.10W) (n/a w/Square)

Voltage

120 120 Volts 277 Volts

Fasteners

Torx Head w/Center pin (2)

3 Phillips-head Fasteners (2)

Option

WL Wet Location Listed

Packaging

SP** Split Packaging (min. quantity 10 pcs)

- † n/a with clear lens
- * Internal Louver (L) available with clear lens option only
- **Rough-In Box (Box 1), Fixture Section (Box 2)

FACEPLATE OPTIONS

Full Face

Slotted



Internal Louvre





MEDMASTER SOFTSTEP™ STEPLIGHTS


Patient Room Steplight

MSL SERIES – FABRICATED


DIMENSIONAL DATA

MSLS


FRONT VIEW




SIDE VIEW





WALL CUTOUT




MSLR-H









MSLR-V







DIMENSIONAL DATA (IN INCHES)											
	Α	В	C	D	E	F	G				
MSLS	5.00	5.00	3.25	0.30	3.12	4.63	3.38				
MSLR-H	4.38	7.00	3.25	0.30	3.12	6.63	3.38				
MSLR-V	7.00	4.38	6.50	0.30	3.12	3.38	6.63				

