TEKLINK™ TL1000/2000 FOR SENSCAPE™

Control System Specification

SPG-TL1000/2000 SYSTEM

PRODUCT FEATURES:

- » Wireless OR Wired Communication
- » Configure System through Web Browser
- » Integral Occupancy Detection
- » Report Energy Consumption
- » Monitor Occupancy Events

PROJECT INFORMATION
Job Name
Fixture Type
Catalog Number
Approved by

SPECIFICATIONS:

PRODUCT BRIEF: TekLink T1000 and TL2000 are cloud-based, adaptive lighting control systems that utilize wired and wireless (respectively) communication between system nodes. The system consists mainly of luminaire-integrated lighting controllers (BORGs), integrated Sensors, Bridges, and a Gateway. This specification provides information on the luminaire level control components. Please see the Bridge and Gateway Specification sheet for additional system information.


TEKLINK TL1000/2000 BORG: Integral controllers located in LED luminaires, sensors, and as stand-alone devices; BORGs (Board on Radio Grid) process data and record system activity. The LED luminaires react to changes in the environment based on a programmable lighting schedule. TL1000 BORGs utilize wired (shielded twisted pair) communication to exchange information built on the CAN bus protocol. TL2000 BORGs use wireless communication (900 MHz), designed to the IEEE 802.15.4 standard.


TEKLINK SENSOR: Operates by low-voltage power provided by the BORG or LED driver and provides Microwave (MW) occupancy detection with integral light level sensing. Microwave sensing operates at 5.8 GHz (continuous-wave radar) and provides 360° coverage at various mounting heights and coverage areas (typical coverage pattern listed below).

INSTALLATION: Control components and sensor integrated in to SPG18 housing at factory.


WARRANTY: Limited five (5) year warranty.

DIMENSIONAL DATA





COVERAGE PATTERN



Ceiling mounted detection pattern

NOTE: Occupancy pattern dimensions are maximums, may vary due to environment

