

MEDMASTER™
Patient Room Luminaires
MPCADE SERIES

For additional photometry, go to www.kenall.com

PERFORMANCE

Model	Function	Lamp Type	Initial Delivered Lumens		Input Power (W)	Drive Current (mA)	Estd. L ₇₀ LED Life (Hrs)
			@ 25°C	Efficacy (lm/W)			
MPCADE22	Ambient	25L-30K8	1,705	66	26	94	80,000
		25L-35K8	1,758	68			
		25L-40K8	1,818	70			
		25L-50K8	1,891	73			
	Exam	45L-30K8	3,027	66	46	94	80,000
		45L-35K8	3,121	68			
		45L-40K8	3,227	70			
		45L-50K8	3,356	73			
	Ambient/Exam	25L/45L-30K8	4,763	65	73	94	80,000
		25L/45L-35K8	4,910	67			
		25L/45L-40K8	5,078	70			
		25L/45L-50K8	5,281	72			
MPCADE24	Ambient	45L-30K8	3,854	79	49	94	80,000
		45L-35K8	3,973	81			
		45L-40K8	4,109	84			
		45L-50K8	4,274	87			
	Exam	90L-30K8	6,931	69	100	94	80,000
		90L-35K8	7,145	71			
		90L-40K8	7,389	74			
		90L-50K8	7,684	77			
	Ambient/Exam	45L/90L-30K8	10,728	72	148	94	80,000
		45L/90L-35K8	11,060	75			
		45L/90L-40K8	11,437	77			
		45L/90L-50K8	11,894	80			

Displayed information is for selected luminaires only. Additional wattages and color temperatures are also available. Visit www.kenall.com for additional information.



www.kenall.com | P: 800-4-Kenall | F: 262-891-9701 | 10200 55th Street Kenosha, Wisconsin 53144, USA


A brand of **legrand**

This product complies with the Buy American Act: manufactured in the United States with more than 50% of the component cost of US origin. It may be covered by patents found at www.kenall.com/patents. Content of specification sheets is subject to change; please consult www.kenall.com for current product details. ©2022 Kenall Mfg. Co.

MEDMASTER™
Patient Room Luminaires
MPCADE SERIES

For additional photometry, go to www.kenall.com


Model: MPCADE22-G-1/2-25L/45L-40K8-DCC-DV-IB-AC



Maximum Candela = 1971 Located At Horizontal Angle = 75, Vertical Angle = 5

- 1 - Vertical Plane Through Horizontal Angles (75-255) (Through Max. Cd.)
- 2 - Horizontal Cone Through Vertical Angle (5) (Through Max. Cd.)


Model: MPCADE24-G-1/2-45L/90L-40K8-DCC-DV-IB-AC



Maximum Candela = 4170 Located At Horizontal Angle = 0, Vertical Angle = 0

- 1 - Vertical Plane Through Horizontal Angles (0-180) (Through Max. Cd.)
- 2 - Horizontal Cone Through Vertical Angle (0) (Through Max. Cd.)

DIMENSIONAL DATA



DIMENSIONAL DATA (IN INCHES)

	A	B	C	D	E	F	G	H	I
2x2 T5 (Flange)	5.93	22.60	23.75	22.60	23.75	-	-	-	-
2x2 T8/LED (Flange)	5.93	22.60	23.75	24.13	25.28	-	-	-	-
2x2 T5 (Grid)	5.93	22.60	23.75	22.60	23.75	-	-	-	-
2x2 T8/LED (Grid)	5.93	22.60	23.75	24.00	23.75	-	-	-	-
2x2 T5 (Surface)	5.93	-	-	-	-	22.60	22.60	8.00	12.00
2x2 T8/LED (Surface)	5.93	-	-	-	-	22.60	24.13	8.00	12.00
2x4 T5 (Flange)	5.93	22.60	23.75	46.60	47.75	-	-	-	-
2x4 T8/LED (Flange)	5.93	22.60	23.75	48.13	49.28	-	-	-	-
2x4 T5 (Grid)	5.93	22.60	23.75	46.60	47.75	-	-	-	-
2x4 T8/LED (Grid)	5.93	22.60	23.75	48.00	47.75	-	-	-	-
2x4 T5 (Surface)	5.93	-	-	-	-	22.60	46.60	30.00	12.00
2x4 T8/LED (Surface)	5.93	-	-	-	-	22.60	48.13	30.00	12.00

FLANGE CEILING CUTOUT**

2x2 T5	22.88 x 22.88
2x2 T8/LED	22.88 x 24.38
2x4 T5	22.88 x 46.88
2x4 T8/LED	22.88 x 48.38

**Add .25" to each cut-out dimension when Install Frame (IF) or Plaster Frame (PF) Accessory is specified



www.kenall.com | P: 800-4-Kenall | F: 262-891-9701 | 10200 55th Street Kenosha, Wisconsin 53144, USA

A brand of **legrand**

This product complies with the Buy American Act: manufactured in the United States with more than 50% of the component cost of US origin. It may be covered by patents found at www.kenall.com/patents. Content of specification sheets is subject to change; please consult www.kenall.com for current product details. ©2022 Kenall Mfg. Co.