

Declare. SM

KENALL SIMPLESEAL™ SEALED ENCLOSURE CSSGI SERIES LIGHT FIXTURES Kenall Manufacturing

Final Assembly: KENOSHA, WISCONSIN, USA

Life Expectancy: 10 Year(s)

End of Life Options: Landfill (100%)

Ingredients:

Fabricated Metal part 01 Rev: Carbon Steel; Zinc; **Lighting component 01:** Small Electrical Components - RoHS compliant¹; **Lighting Component 02:** Aluminum Alloy; **Electronic component :** Small Electrical Components - RoHS compliant¹; **Wire - Hardware 01:** Copper; **Polyvinyl chloride;** Tris(2-ethylhexyl) trimellitate; Clay; Octadecanoic acid, calcium salt; Antimony oxide (Antimony trioxide); **Hardware 2:** Steel; **Electrical component - Hardware 03:** Carbonic acid, polymer with 4,4'-(1-methylethylidene)bis[phenol]; Stainless Steel; Copper; Tin, Organic; Nylon 6; **Foam:** Clay; SBR; Bicyclo[2.2.1]hept-2-ene, 5-ethylidene-, polymer with ethene and 1-propene; Alkanes, C20-28, chloro; **Electronic component - Hardware04:** Steel; **Wire - Hardware 02:** Small Electrical Components - RoHS compliant¹

¹LBC Temp Exception RL-002 - Small Electrical Components

Living Building Challenge Criteria:

I-13 Red List:

- | | |
|--|-----------------------------|
| <input type="checkbox"/> LBC Red List Free | % Disclosed: 100% at 100ppm |
| <input type="checkbox"/> LBC Red List Approved | VOC Content: Not Applicable |
| <input checked="" type="checkbox"/> Declared | |

I-10 Interior Performance: Not Applicable

I-14 Responsible Sourcing: Not Applicable

KEN-0002

EXP. 01 FEB 2027

Original Issue Date: 2026

Third
Party
Verified