



TRANSPORTATION

# New Helos™ HPG14 (Series) for Parking The New Featherweight Champion



## HPG14 Series

- Delivered lumen range: 3,941 – 10,084 lm
- Input power: 36 – 79W
- Efficacy: 110 – 135 lm/W
- Unique hexagonal light guide with edge-lit LED light engine
- TekLink™ TL200 option, provides simple, wireless zonal control via occupancy sensors
- No commissioning required
- Unique security key for added network protection
- No uncomfortable “cascade effect” lighting

Nominal size:	14" diameter
Installation type:	direct-to-surface over recessed electrical box; quick-mount surface or recessed electrical box; trunion or pendant
Lamp type:	LED

**Kenall's Helos™** parking luminaire series is designed to make your lighting, and its installation into your parking structure, easier. This new edge-lit design features a flat illuminance plane that provides superior lighting performance, regardless of mounting type.

**At just 7 pounds,** Helos weighs less than half of its closest competitor, making it economical to ship and easy to install. Best of all, Helos can go straight from box to ceiling, with simple, wireless, zonal **TekLink TL200** controls, and no commissioning. System adjustments can be managed via an intuitive mobile app.

And that's just three of the many ways Helos makes your next parking luminaire choice an easy one.



Direct surface mount only



www.kenall.com | P: 800-4-Kenall | F: 262-891-9701 | 10200 55th Street Kenosha, Wisconsin 53144

A brand of **legrand**

This product complies with the Buy American Act: manufactured in the United States with more than 50% of the component cost of US origin. It may be covered by patents found at www.kenall.com/patents. Content of specification sheets is subject to change; please consult www.kenall.com for current product details.