

HERCULUX™

H99 SERIES – MEDIUM PROFILE HOUSING

PRODUCT FEATURES:

- » Surface mount – ceiling; 13"W×13"L×6"D
- » One-piece heavy duty die-cast housing
- » UV-stabilized, injection molded polycarbonate lens
- » Stainless steel Torx® fasteners



PROJECT INFORMATION

Job Name _____

Fixture Type _____

Catalog Number _____

Approved by _____

SPECIFICATIONS

HOUSING: One-piece heavy duty die-cast, low-copper aluminum housing. Housing flange interlocks around refractor producing maximum moisture deflection and resistance to prying. Housing provided with four standoff mounting holes. One 3/4" IPS tapped hole on back of housing. Two 3/4" IPS tapped and plugged holes on sides of housing – see Cross Section/Details. Standard housing in dark bronze TGIC polyester powder coat – 5-stage pre-treatment.

REFLECTOR: High reflectance painted aluminum.

LENS: One-piece wraparound lens (UV-stabilized, high impact, virgin injection molded polycarbonate). Smooth exterior, prismatic interior. Nominal thickness: 0.125".

VISOR: One-piece injection molded opaque dark bronze polycarbonate (UV-stabilized). Optional finishes to match housing. Nominal thickness .125". Visor allows for full-cutoff light output.

GASKET: Die-cut closed cell neoprene gasket seals die-cast housing to ceiling surface. Lens inset into housing and sealed to integral ledge with one "O" ring closed cell silicone gasket.

HARDWARE: Four stainless steel Torx® with center pin fasteners secure lens/visor to housing.

ELECTRICAL: Available in 3500K, 4000K, and 5000K color temperatures, 80 CRI. 120-277VAC or 347VAC, 50/60Hz electrical input with high power factor electronic, constant-current driver (>.90 PF). Standard 0-10V dimming with 1-100% range; maximum driver source of 200 µA.

INSTALLATION: Standard four-point mounting required for Peace of Mind Guarantee®.

PHOTOMETRICS: Photometry tested to the IESNA LM-79-08 standard by an ILAC/ISO17025 accredited laboratory. For additional photometric data, please go to www.kenall.com.

WARRANTY: Limited five (5) year LED warranty. [Peace of Mind Guarantee against breakage.](#)

LISTINGS: Luminaire is certified to UL Standards by Intertek Testing Laboratory for Wet Location.



ORDERING INFORMATION (Ex: H99DSM-PP-MB-25L40K-DV)

Model	Lens Type	Finish	Lamp Type	Voltage	Options	Accessories
H99DSM	PP					
	Lens Type		Lamp Type		Options	
	PP Pearlescent Polycarbonate		15L35K 15 Watt 3500K LED		BPC Photo Control – Button Type (120 or 277V only)	
			15L40K 15 Watt 4000K LED		FS Single Fuse & Holder	
	Finish		15L50K 15 Watt 5000K LED		Accessory	
	DB Dark Bronze		25L35K 25 Watt 3500K LED		9500 Torx® Screwdriver	
	FG Forest Green		25L40K 25 Watt 4000K LED		▼ n/a with BPC	
	LG Light Gray		25L50K 25 Watt 5000K LED			
	MB Matte Black					
	MW Matte White		Voltage			
	SL Silver		120 120 Volts			
	CC Custom Color (Consult factory)		277 277 Volts			
			347 347 Volts			
			DV 120-277 Volts			



www.kenall.com | P: 800-4-Kenall | F: 262-891-9701 | 10200 55th Street Kenosha, Wisconsin 53144, USA

This product complies with the Buy American Act: manufactured in the United States with more than 50% of the component cost of US origin. It may be covered by patents found at www.kenall.com/patents. Content of specification sheets is subject to change; please consult www.kenall.com for current product details. ©2019 Kenall Mfg. Co.

A brand of **legrand**

HERCULUX™


H99 SERIES – MEDIUM PROFILE HOUSING

PERFORMANCE

Lamp Type	Initial Delivered Lumens		Input Power (W)	Drive Current (mA)	Estd. L70 LED Life (Hrs)
	@ 25°C	Efficacy (lm/W)			
15L35K	1774	90	20	54	100,000
15L40K	1774	90	20	54	100,000
15L50K	1934	98	20	54	100,000
25L35K	2601	88	30	90	100,000
25L40K	2601	88	30	90	100,000
25L50K	2835	96	30	90	100,000

Info subject to change. Visit www.kenall.com for IES files and additional information.

Model: H99DSM-PP-MW-25L40K-DV




Max Candela = 816 Located At Horizontal Angle = 0, Vertical Angle = 0

- 1 - Vertical Plane Through Horizontal Angles (0-180) (Through Max. Cd.)
- 2 - Horizontal Cone Through Vertical Angle (0) (Through Max. Cd.)

DIMENSIONAL DATA

CROSS SECTION / DETAILS



BACK MOUNTING VIEW

