

# LIGHTMATE™

## L68L SERIES (3600)

### PRODUCT FEATURES:

- » Ceiling or wall mount – 6"W×8"H×4"D
- » 16-gauge cold rolled steel baseplate
- » One-piece, UV-stabilized polycarbonate lens
- » Peace of Mind Guarantee® against breakage



### PROJECT INFORMATION

Job Name \_\_\_\_\_

Fixture Type \_\_\_\_\_

Catalog Number \_\_\_\_\_

Approved by \_\_\_\_\_

### SPECIFICATIONS

**LENS/HOUSING:** One-piece wraparound lens/housing (UV-stabilized, high impact, virgin injection molded polycarbonate). High efficiency Pearlescent lens. Nominal thickness .125".

**BASEPLATE:** 16-gauge CRS. Baseplate provided with four-point mounting holes, one wireway hole – see Cross Section/Details. White TGIC polyester powder coat – 5-stage pre-treatment. Salt spray test: 1,000 hours; Reflectance: 92%. See Options or Accessories for marine grade aluminum baseplate (AL), convenience outlet adapter (CO) and die-cast aluminum surface conduit adapter (SA).

**GASKET:** Die-cut closed cell neoprene gasket seals lens/housing to mounting surface.

**HARDWARE:** Two stainless steel Torx® with center pin fasteners secure lens/housing to baseplate.

**ELECTRICAL:** Medium base shock absorbing lamp socket .

**INSTALLATION:** Fixture must be installed lamp base up. Standard four-point mounting required for Peace of Mind Guarantee®.

**WARRANTY:** Limited one (1) year Kenall fluorescent warranty.

**LISTINGS:** UL and CUL listed for Wet Location.



### ORDERING INFORMATION (Ex: L68L-P-75I-1-120-FS)

| Model       | Lens Type | Lamp Type  | Lamp Qty | Voltage    | Options | Accessories |
|-------------|-----------|------------|----------|------------|---------|-------------|
| <b>L68L</b> | <b>P</b>  | <b>75I</b> | <b>1</b> | <b>120</b> |         |             |

#### Lens Type

**P** Pearlescent Polycarbonate

#### Lamp Quantity

**1** One Lamp

#### Options

**AL** Marine Grade Aluminum Baseplate  
**FS** Single Fuse & Holder (with SA or CO only)  
**MS4** Four Torx® Fasteners  
**PH** Phillips Head Fasteners

#### Lamp Type

**75I** 75 Watt Incandescent (A19)

#### Voltage


**120** 120 Volts

#### Accessories


**CO** Convenience Outlet Adapter – Non-GFI Receptacle (9070)  
**SA** Surface Adapter (9050)  
**9500** Torx® Screwdriver

### DIMENSIONAL DATA


#### CROSS SECTION/DETAILS




#### BASEPLATE (CRS OR AL)



#### CONVENIENCE OUTLET ADAPTER (CO)



#### SURFACE ADAPTER (SA)



www.kenall.com | P: 800-4-Kenall | F: 262-891-9701 | 10200 55th Street Kenosha, Wisconsin 53144, USA

This product complies with the Buy American Act: manufactured in the United States with more than 50% of the component cost of US origin. It may be covered by patents found at [www.kenall.com/patents](http://www.kenall.com/patents). Content of specification sheets is subject to change; please consult [www.kenall.com](http://www.kenall.com) for current product details. ©2019 Kenall Mfg. Co.

A brand of **legrand**

L68L-100918