

MILLENIUM METREX™

METSR SERIES

PRODUCT FEATURES:

- » Semi-recessed wall mount – Single Face
- » Indirect Red or Green LED
- » Internal Battery Backup System
- » 20-gauge cold rolled steel housing
- » Self diagnostic testing features



PROJECT INFORMATION

Job Name _____

Fixture Type _____

Catalog Number _____

Approved by _____

SPECIFICATIONS

HOUSING: 20-gauge CRS. Hole-free one-piece seam welded construction.

FRAME: One-piece die-formed prime grade 16-gauge material as specified – see Ordering Information. Corners continuously seam welded and smooth with no post grinding (TIG).

LENS: External panel .188" thick clear polycarbonate.

LEGEND: Legend illuminated by internal high output LEDs. Lettering six inches high with .750" stroke. Polycarbonate red or green filter panels. High impact, punched, formed and painted sheet metal stencil and field selectable chevron inserts.

FASTENERS: Hardened security screws as specified – see ordering information.

FINISH: TGIC polyester powder coat – 5-stage pre-treatment. Salt spray test: 1,000 hours; Reflectance: 92%. See Options for black exterior.

ELECTRICAL: 624 nm Red or 527 nm Green LED light source. Electrical components mounted to removable high impact, injection molded polycarbonate chassis. Remote Exit Ready – can power one Kenall METSS Satellite Exit.

OPTIONS: Sealed nickel-cadmium Emergency Battery Pack (EL) with standard deep cycle battery conditioning, self test and self diagnostic circuitry, remote laser activated test switch, protected mechanical test switch and status indicator. Provides 120 minutes of emergency operation. Emergency Battery Pack (EL) suitable for 10°C to 45°C (50°F to 113°F). Cold Weather Emergency Battery Pack (CEL) suitable for -45°C to 45°C (-49°F to 113°F). (When used with a Kenall METSS, this fixture provides 90 minutes of emergency operation.)


LISTINGS: UL and CUL listed for Wet Location. UL certified IP65 in compliance with IEC 60598. Meets or exceeds UL924 and NFPA 101 standards. Meets or exceeds CSA and NRCAN requirements.



ORDERING INFORMATION (Ex: METSR-1-R-DT-1-EL)

Model	Frame Material	Legend Color	Voltage	Fastener	Options	Accessories
METSR						
Frame Material		Legend Color		Fasteners		Accessories
1	16-Ga CRS (Painted)	G	Green	1	Torx® Head w/ Center Pin	LP Laser Pointer
4	16-Ga SS (Painted)	R	Red	2	Allen Head w/ Center Pin	9500 Torx® with center pin Screwdriver
7	16-Ga SS (Brushed)					
		Voltage		Options		
		DT	120/277 Volts	BLK	Black Exterior Frame and Exit Face	
		DTC	120/347 Volts	CEL	Cold Weather Emergency Battery Pack	
				EL	Standard Emergency Battery Pack	
				XAC	Auxiliary AC Supply (matches voltage selection)	
				XDC	Auxiliary DC Supply (6-24 volts)	

DIMENSIONAL DATA



www.kenall.com | P: 800-4-Kenall | F: 262-891-9701 | 10200 55th Street Kenosha, Wisconsin 53144, USA

This product complies with the Buy American Act: manufactured in the United States with more than 50% of the component cost of US origin. It may be covered by patents found at www.kenall.com/patents. Content of specification sheets is subject to change; please consult www.kenall.com for current product details. ©2019 Kenall Mfg. Co.

A brand of **legrand**