

MIGHTY MAC™

SCC SERIES

PRODUCT FEATURES:

- » Surface ceiling mount – 20" x 24", 20" x 48"
- » TIG welded housing with no post grinding for additional strength
- » Vertically adjustable Z bracket with thru-studs spaced 6" (15.24cm) apart
- » Full length concealed internal piano hinge



PROJECT INFORMATION

Job Name _____

Fixture Type _____

Catalog Number _____

Approved by _____

SPECIFICATIONS

HOUSING: One-piece die-formed prime grade material as specified – see ordering information. Corners continuously seam welded and smooth with no post grinding (TIG). Clamshell housing resistant to penetration and contraband concealment.

BASEPLATE: Prime grade material as specified – see ordering information. Die-formed blade trap (1/4" minimum) prevents contraband concealment and access. Embossed standoffs prevent distortion.

LENS: As specified – maximum thickness .875" – see ordering information. Kenall recommends a prismatic inner lens and a clear outer lens. Two clear lenses used in combination cannot be provided.

LENS RETENTION: Vertically adjustable continuous "Z" brackets of prime grade material, secured to housing via thru-studs (6" maximum spacing).

HINGE: Full length continuous heavy gauge internal piano hinge (1/2" knuckle/1/8" diameter pin) standard. Pin secured to knuckle. Hinge welded to housing and mounts to baseplate via keyholes.

FASTENERS: Hardened security screws as specified – see ordering information. Fully recessed.

FINISH: TGIC polyester powder coat – 5-stage pre-treatment. Salt spray test: 1,000 hours; Reflectance: 92%.

LAMPS: Quantity and type as specified – see ordering information. Lamps supplied by others.

BALLAST: Quantity and type as specified – see ordering information. All ballasts UL listed class P. Optional removable reflector/lamp/ballast tray with quick disconnect.

LUMINOUS SEAL: Polyurethane foam prevents light leaks from luminaire base.

INSTALLATION: Fixture not suitable for Surface Conduit or Continuous Row Mounting.

PHOTOMETRICS: Efficiency of SCC4-0/0-332-IS-1-120-1/A-1 = 69.2%. For photometric information, go to www.kenall.com.

WARRANTY: 1 Year Warranty for Kenall fluorescent lighting products.

LISTINGS: UL and CUL listed for damp locations.



ORDERING INFORMATION (Ex: SCC-2-0/0-2-17-IS-1-120-1/B-1)

Model	Size	Housing/Base	Lamp Qty	Lamp Type	Ballast Type	Ballast Qty	Voltage	Lens (Inner/Outer)	Fasteners	Options
SCC		/						/		
Nominal Size		Lamp Quantity		Ballast Quantity		Fasteners				
2	20" x 24"	2	Two	1	One	1	Torx® Head w/ Center Pin			
4	20" x 48"	3	Three	2	Two	2	Allen Head w/ Center Pin			
4		4	Four							
Housing/Base Material		Lamp Type		Voltage		Options				
0	14-Ga CRS (Painted White)	2'	Nominal Length	120	120 Volts	EL	Standard Lumen EL Pack			
1	16-Ga CRS (Painted White)	17	F17T8	277	277 Volts	PEL	High Lumen EL Pack			
3	14-Ga SS (Painted White)	4'	Nominal Length	347	347 Volts	SEL	Specified EL Pack			
4	16-Ga SS (Painted White)	32	F32T8			DLN	LED Night Light w/Light Level Control (100% - 20%; voltage-specific selection required)			
6*	14-Ga SS (Brushed)	Ballast Type		Lens (Inner/Outer)‡		FS				
7*	16-Ga SS (Brushed)	IS	Instant Start Electronic <10% THD (T8)	0	No Lens	Single Fuse & Holder				
9	12-Ga CRS (Painted White)	RS	Rapid Start Electronic <10% THD (CFL, T8)	1	.125" Prismatic Acrylic	RGT		Removable Gear Tray		
		SB	Specified Ballast	2	.125" Prismatic Polycarbonate	SK		Speaker Housing Extension		
				3	.125" Textured Polycarbonate	TN		PL Night Light – 5/7/9 Watt (Lamp supplied by other) (120/277V only)		
				G	.125" Clear Polycarbonate	UV		Ultraviolet Filter		
				4	.156" Prismatic Polycarbonate					
				TG	.125" Textured Tempered Glass					
				6	.187" Prismatic Polycarbonate					
				7	.187" Clear Polycarbonate					
				8	.187" Clear Tempered Glass					
				9	.250" Clear Polycarbonate					
				A	.250" Clear Tempered Glass					
				B	.375" Clear Polycarbonate					
				C	.375" Clear Tempered Glass					
				J	.500" Clear Polycarbonate					
				P	.500" Clear Tempered Glass					
				N	.750" Clear Tempered Glass					



www.kenall.com | P: 800-4-Kenall | F: 262-891-9701 | 10200 55th Street Kenosha, Wisconsin 53144, USA

A brand of **legrand**

This product complies with the Buy American Act: manufactured in the United States with more than 50% of the component cost of US origin. It may be covered by patents found at www.kenall.com/patents. Content of specification sheets is subject to change; please consult www.kenall.com for current product details. ©2019 Kenall Mfg. Co.

SCC-061820

MIGHTY MAC™

SCC SERIES

DIMENSIONAL DATA

