

# TEKDEK™

## TD13 SERIES – LF

### PRODUCT FEATURES:

- » Surface ceiling mount – 48" (122 cm) & 96" (244 cm) lengths
- » UV-stabilized prismatic polycarbonate lens
- » Batwing distribution for uniform illumination



### PROJECT INFORMATION

Job Name \_\_\_\_\_

Fixture Type \_\_\_\_\_

Catalog Number \_\_\_\_\_

Approved by \_\_\_\_\_

### SPECIFICATIONS:

**BASEPLATE:** One piece die-formed 20-gauge steel provided with 6-point (4' (122 cm) luminaire) or 8-point (8' (244 cm) luminaire) mounting and one wiring hole. TGIC polyester powder coat – 5-stage pre-treatment. Salt spray test: 1,000 hours. See Ordering Information for available finishes.

**REFLECTOR:** Parabolic die-formed specular aluminum (T8) and high reflectance white (T5HO) provides batwing distribution.

**LENS:** UV-stabilized extruded prismatic polycarbonate lens with a smooth exterior. Nominal thickness .100" (.25 cm). Secured in gasketed channel with Torx® fasteners – (10) for 48" (122 cm) length; (15) for 96" (244 cm) length. Self-hinging design (no lanyard required).

**ELECTRICAL:** See Ordering Information for ballasts options and optional equipment. Lamps by others.

**WARRANTY:** Limited one (1) year Kenall fluorescent warranty.


**LISTINGS:** Luminaire is certified to UL Standards by Intertek Testing Laboratory for Wet location. IP65 per IEC 60598.



### ORDERING INFORMATION (Ex: TD13-48-MW-2H-2-54-IS-120)

Model	Length	Finish	Baseplate Mtrl	Lamp Qty/Type	Ballast Type	Voltage	Options
<b>TD13</b>							
	<b>Length</b>		<b>Baseplate Material</b>			<b>Voltage</b>	
	<b>48</b> 48" (122 cm)		<b>2H</b> 20-Ga CRS; Painted			<b>120</b> 120 Volts	
	<b>96</b> 96" (244 cm)		<b>P5H</b> 20-Ga 304SS; Painted			<b>277</b> 277 Volts	
	<b>Finish</b>		<b>Lamp Quantity/Type (Cross Section)</b>			<b>347</b> 347 Volts (60Hz, 25 C° ambient only)	
	<b>FG</b> Forest Green		<b>2-32</b> Two F32T8			<b>DV</b> 120-277 Volts	
	<b>GW</b> Reflectance White		<b>3-32</b> Three F32T8			<b>Options</b>	
	<b>LG</b> Light Gray		<b>2-54</b> Two F54T5HO			<b>FS</b> Single Fuse & Holder	
	<b>MB</b> Matte Black		<b>2-54A</b> Two F54T5HO amalgam			<b>PH</b> Phillips Fasteners (n/a with Peace of Mind Guarantee®)	
	<b>MW</b> Matte White					<b>SA</b> Surface Adapter (required for conduit entry)	
	<b>SL</b> Silver		<b>Ballast Type</b>				
	<b>CC</b> Custom Color (Consult factory)		<b>IS</b> Instant Start Electronic <10% THD (T8)				
			<b>RS</b> Rapid Start Electronic <10% THD (T8,T5HO)				
			<b>SB</b> Specified Ballast				

### DIMENSIONAL DATA



DIMENSIONAL DATA (IN INCHES)								
	A	B	C	D	E	F	G	
<b>T5 48" (1.22 m)</b>	13.13 (33.35 cm)	6.13 (15.57 cm)	13.07 (33.20 cm)	8.00 (20.32 cm)	46.86 (119 cm)	40.00 (102 cm)	n/a	n/a
<b>T5 96" (2.44 m)</b>	13.13 (33.35 cm)	6.13 (15.57 cm)	13.13 (33.35 cm)	8.00 (20.32 cm)	93.43 (237 cm)	41.75 (106 cm)	29.50 (74.93 cm)	
<b>T8 48" (1.22 m)</b>	13.13 (33.35 cm)	6.13 (15.57 cm)	13.07 (33.20 cm)	8.00 (20.32 cm)	48.50 (123 cm)	40.00 (102 cm)	n/a	n/a
<b>T8 96" (2.44 m)</b>	13.13 (33.35 cm)	6.13 (15.57 cm)	13.13 (33.35 cm)	8.00 (20.32 cm)	97.00 (246 cm)	43.50 (110 cm)	30.00 (76.20 cm)	



www.kenall.com | P: 800-4-Kenall | F: 262-891-9700 | 10200 55th Street Kenosha, Wisconsin 53144, USA  
 This product can comply with the latest domestic preference legislation, such as the Buy American Act (BAA), Trade Agreement Act (TAA), Build America, Buy America Act (BABA), and others. It may be covered by patents found at www.kenall.com/patents. Content of specification sheets is subject to change; please consult www.kenall.com for current product details. ©2024 Kenall Mfg. Co.

A brand of **legrand**