MEDMASTER SOFTSTEP™ STEPLIGHTS

Patient Room Steplight

MSL SERIES – FABRICATED

PRODUCT FEATURES:

- » Recessed wall mount Oval and Rectangle available in horizontal or vertical orientation
- » NSF2 listing for cleanability
- » White, Amber, Blue or Red LED lamp options
- » ADA Compliant



PROJECT INFORMATION Job Name Fixture Type Catalog Number. Approved by

SPECIFICATIONS

HOUSING: 18-gauge CRS. White TGIC polyester powder coat - 5-stage pre-treatment. Salt spray test: 1,000 hours; Reflectance: 92%. Four .875" knockouts.

FACEPLATE: 18-gauge CRS (powder coated) or Type 304 Brushed Stainless Steel. Faceplate secured to housing with stainless steel screws. Internal louver is positioned behind lens for easy cleaning of entire faceplate. See Faceplate Finish in Ordering Information for color selection.

LENS: Polycarbonate, acrylic or tempered glass lens. Polycarbonate and acrylic lens available in clear, prismatic or translucent white. Tempered glass available in clear or prismatic.

ELECTRICAL: 120VAC or 277VAC LED technology. Available in white, red, amber and blue.

INSTALLATION: Two adjustable mounting brackets for new construction.

PHOTOMETRICS: Photometry tested to the IESNA LM-79-08 standard by an ILAC/ISO17025 accredited laboratory. For additional photometric information, go to www.kenall.com.

WARRANTY: Limited five (5) year LED warranty.

LISTINGS: UL and CUL Listed for Damp Location. See Option for Wet Location listing. NSF2 Splash/Non-Food Zone.



ORDERING INFORMATION (Ex: MSLO-H-F-0-GW-CP-WLL-120-2)

Faceplate Faceplate Material Faceplate Finish Model Lens Type Lamp Type Voltage Fasteners Option Packaging

Model

MSLR-V Rectangle Vertical Rectangle Horizontal MSLR-H MSLS

Square

Faceplate

Full Face Internal Louver

Slotted (n/a on Oval models) S†

Faceplate Material

18-Ga CRS (Painted) 18-Ga Type 304 SS Brushed **Faceplate Finish**

GW Gloss White Antimicrobial MW Matte White Antimicrobial MB Matte Black Antimicrobial

BE Beige

DB Dark Bronze LG Light Gray

I۷ Ivory

cs

Cool Satin Painted Anodized WS Warm Satin Painted Anodized

BSS Brushed SS

Lens Type

Polycarbonate

Clear Polycarbonate

Pearlescent Polycarbonate 2 .125" #12 Prismatic Polycarbonate

<u>Acrylic</u>

.125" Clear High Impact Acrylic

PIA Pearlescent Acrylic

.125" #12 Prismatic High Impact Acrylic U

Tempered Glass

.187" Clear Tempered Glass .156" Textured Tempered Glass TG

Lamp Type Low Lumen

WLL 4100K White Low Lumen LED (0.05A/0.55W)

ALL Amber LED (0.05A/0.50W) Red LED (0.05A/0.50W) RLL

BLL Blue LED (0.10A/1.20W)

WHL 4100K White High Lumen LED (0.10A/1.10W) (n/a w/Square)

Voltage

120 120 Volts 277 277 Volts

Fasteners

Torx Head w/Center pin (2) 3

Phillips-head Fasteners (2)

Option

Wet Location Listed

Packaging

Split Packaging (min. quantity 10 pcs)

† n/a with clear lens

* Internal Louver (L) available with clear lens option only

**Rough-In Box (Box 1), Fixture Section (Box 2)

MEDMASTER SOFTSTEP™ STEPLIGHTS


Patient Room Steplight

MSL SERIES – FABRICATED


DIMENSIONAL DATA

MSLS


FRONT VIEW




SIDE VIEW





WALL CUTOUT




MSLR-H









MSLR-V







DIMENSIONAL DATA (IN INCHES)							
	Α	В	C	D	E	F	G
MSLS	5.00	5.00	3.25	0.30	3.12	4.63	3.38
MSLR-H	4.38	7.00	3.25	0.30	3.12	6.63	3.38
MSLR-V	7.00	4.38	6.50	0.30	3.12	3.38	6.63



